



- Mobile Document Destruction

- On-Site Security Shredding

EV60DD

PERFORMANCE CHARACTERISTICS:

63 Kw/ 84 Hp Maximum Power
28—30 Rpm Cutter Speed Rotation
8, 12 or 16 mm Shred Width
512 mm x 375 mm Cutting Chamber Opening
18,9 m/min Cutting Speed
2000 Kg per hour*
Standard Layout** includes Bin-Tipper In-feed
Standard Layout** includes Auger Out-feed
Electronic over Hydraulic Controls
Mobile Applications



* Normal Office Paper Under Ideal Conditions

** We have many variations to the standard layout available. Each quotation includes a full description of supplied items
Specifications are subject to change without notice. Contact your nearest distributor/ agent for up-to-date specifications prior to purchase.

EV60DD

TECHNICAL SPECIFICATIONS:



PHYSICAL DIMENSIONS:

Total Height:	1400 mm
Total Length:	2180 mm
Total Width:	900 mm
Hopper Slot Opening:	150 x 600 mm
Shredder Chamber Opening:	512 x 375 mm

SHREDDER NAME:	EV60DD (Hydraulic)
Power Source	63Kw PTO or Direct Drive
Number of Gearboxes	2
Type of Gearboxes	1 x Planetary Reduction, 1 x Splitter
Cutter Width	8mm, 12mm or 16mm
No. of Hooks per cutter	3
Cutter Diameter	200mm
Distance between Shafts	165mm
Hex Shaft Diameter	77mm AF
Critical Shaft Length	512mm (Paper)
Cutter Chamber Opening	512mm x 375mm
Cutting Chamber Height	250mm
Hopper Entrance Height	1200mm
Total Height	1400mm
Floor Footprint Dimensions	2180mm x 900mm
Weight	2400 Kg
Equipment Included in Standard Layout**	EV60 Shredder, Bin-Tipper, Sorting Conveyor Belt, Auger Compactor, Hydraulic Pumps, Motors and Controls
Capacity/ Throughput Rate	2000 kg per hour*
Cutting Tip Force	16000 Kg/ 35200 lbs per meter of shaft length

* Normal Office Paper Under Ideal Conditions

** We have many variations to the standard layout available. Each quotation includes a full description of supplied items
Specifications are subject to change without notice. Contact your nearest distributor/ agent for up-to-date specifications prior to purchase.